



### Overhaul Ball DIN Hook

Stock No.	Model No.	Type	Hook DIN	WLL (tons)	Dimensions (mm)							Weight (kgs)
					A	B	O	Q	R	T	TL	
56.0020.003.34	OHB 3,2.20.C	Eye-Hook	2.5 P	3.2	145	145	41	27	30	22	441	20
56.0060.003.34	OHB 3,2.60.C	Eye-Hook	2.5 P	3.2	200	225	41	27	30	22	521	60
56.0080.003.34	OHB 3,2.80.C	Eye-Hook	2.5 P	3.2	220	255	41	27	30	22	551	80
56.0100.003.34	OHB 3,2.100.C	Eye-Hook	2.5 P	3.2	240	275	41	27	30	22	571	100
56.0040.005.34	OHB 5.40.C	Eye-Hook	2.5 P	5	170	190	41	32	35	28	500	40
56.0080.005.34	OHB 5.80.C	Eye-Hook	2.5 P	5	220	255	41	32	35	28	566	80
56.0100.005.34	OHB 5.100.C	Eye-Hook	2.5 P	5	240	275	41	32	35	28	586	100
56.0130.005.34	OHB 5.130.C	Eye-Hook	2.5 P	5	260	310	41	32	35	28	621	130
56.0100.006.34	OHB 6,3.100.C	Eye-Hook	4 P	6.3	240	275	49	37	45	35	630	100
56.0130.006.34	OHB 6,3.130.C	Eye-Hook	4 P	6.3	260	310	49	37	45	35	665	130
56.0170.006.34	OHB 6,3.170.C	Eye-Hook	4 P	6.3	280	340	49	37	45	35	695	170
56.0040.008.34	OHB 8.040.C	Eye-Hook	4 P	8	170	190	49	37	45	35	556	40
56.0130.008.34	OHB 8.130.C	Eye-Hook	4 P	8	260	310	49	37	45	35	665	130
56.0170.008.34	OHB 8.170.C	Eye-Hook	4 P	8	280	340	49	37	45	35	695	170
56.0210.008.34	OHB 8.210.C	Eye-Hook	4 P	8	300	335	49	37	45	35	735	210
56.0045.010.34	OHB 10.045.C	Eye-Hook	5 P	10	170	190	55	43	50	40	643	45
56.0170.010.34	OHB 10.170.C	Eye-Hook	5 P	10	280	340	55	43	50	40	747	170
56.0210.010.34	OHB 10.210.C	Eye-Hook	5 P	10	300	335	55	43	50	40	787	210
56.0250.010.34	OHB 10.250.C	Eye-Hook	5 P	10	320	400	55	43	50	40	807	250
56.0045.013.34	OHB 12,5.045.C	Eye-Hook	5 P	12.5	170	190	55	52	60	45	663	45
56.0210.013.34	OHB 12,5.210.C	Eye-Hook	5 P	12.5	300	355	55	52	60	45	807	210
56.0250.013.34	OHB 12,5.250.C	Eye-Hook	5 P	12.5	320	400	55	52	60	45	827	250
56.0350.013.34	OHB 12,5.350.C	Eye-Hook	5 P	12.5	350	450	55	52	60	45	877	350
56.0050.016.34	OHB 16.050.C	Eye-Hook	6 P	16	170	190	59	59	70	50	723	50
56.0250.016.34	OHB 16.250.C	Eye-Hook	6 P	16	320	400	59	59	70	50	934	250
56.0350.016.34	OHB 16.350.C	Eye-Hook	6 P	16	350	450	59	59	70	50	984	350
56.0500.016.34	OHB 16.500.C	Eye-Hook	6 P	16	410	500	59	59	70	50	1034	500
56.0350.020.34	OHB 20.350.C	Eye-Hook	8 P	20	350	450	69	65	75	60	1022	350
56.0500.020.34	OHB 20.500.C	Eye-Hook	8 P	20	410	500	69	65	75	60	1072	500
56.0650.020.34	OHB 20.650.C	Eye-Hook	8 P	20	430	550	69	65	75	60	1122	650

Minimum Ultimate Strength = 4 x WLL.

Ball swivel with roller thrust bearing, grease lubricated. Ball swivel for higher WLL and of higher weights available on request. Hole can be made larger on request. Standard painted in yellow. On request, swivels can be made suitable for subsea use.